



| TIRE MARK | COMPOUND/HARDNESS | RECOMMENDED USE | OPTIMAL TEMP. |
|-----------|---------------------------|-----------------------|---------------|
| | G8 ROCK | ROCK TERRAIN | (>60°F) |
| | PR SUPER SOFT ROCK | SLICK ROCK TERRAIN | (<60°F) |
| | MC CLAY | INDOOR CLAY | (ALL) |
| | M2 MEDIUM | OUTDOOR | (>90°F) |
| | M3 SOFT | INDOOR/OUTDOOR | (70°F - 90°F) |
| | M4 SUPER SOFT | INDOOR/OUTDOOR | (<70°F) |
| | S2 MEDIUM | DRY SURFACE/HIGH WEAR | (>90°F) |
| | S3 SOFT | DRY SURFACE | (70°F - 90°F) |
| | S4 SUPER SOFT | DRY SURFACE | (<70°F) |
| | Z3 MED. CARPET | CARPET (GRAY)/ASTRO | (>90°F) |
| | Z4 SOFT CARPET | CARPET (BLACK)/ASTRO | (70°F - 90°F) |

WET SURFACE

| | SUPER SOFT | | SOFT | | MEDIUM | | FIRM | |
|----------------------------|---------------------|--|---------------------------|--|-----------------|--|------|--|
| | <60° | | IDEAL SURFACE TEMPERATURE | | | | >90° | |
| | WET SURFACE CONTROL | | | | WEAR RESISTANCE | | | |
| Off-Road, Clay, A/T | | | | | | | | |
| Off-Road, Drag | | | | | | | | |
| Rock Crawling | | | | | | | | |
| Carpet | | | | | | | | |